

UK Declaration of Conformity

Nr : PKR3338500-02

Products identification :

Type of products : Limit switches

Trademark : **Telemecanique Sensors**

Models : **XCMH...**
(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)** and **Yageo TMSS UK Limited (UK Representative)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following Regulation(s) :

Electrical Equipment (Safety) Regulations : **SI 2016 No. 1101**

Electromagnetic Compatibility Regulations : **SI 2016 No. 1091**

Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 : **SI 2012 No. 3032**

Product's conformity has been assessed by applying the following designated standard(s) :

BS EN 60947-5-1:2017 + AC:2020

BS EN IEC 63000:2018

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.



Tony KUMETA

General Manager, UK&I

Issued at : Harrogate – UNITED KINGDOM

Emission date : February 27th, 2024

Manufacturer :
TMSS France

Tour Egho – 2 avenue Gambetta
92400 Courbevoie – FRANCE

UK Representative :
Yageo TMSS UK Limited

2 North Park Road
Harrogate, HG1 5PA – UNITED KINGDOM

Technical Documentation authority :
TMSS France

Boulevard Salvador Allende – ZI n°3
16340 L'Isle d'Espagnac – FRANCE

Appendix

Nr : PKR3338500-02

List of product models covered by the present UK Declaration of Conformity

XCMH	21	15	L2	F	0	SR	TQ
I	II	III	IV	V	VI	VII	VIII

I	Body type	
	XCMH	: Optimum miniature plastic limit switch
II	Contact block type	
	21	: NO+NC snap action
	29	: NC+NC snap action
III	Operating head type	
	nn	: All existing ZCE heads (nn = 02 for ZCE02, nn = 07 for ZCE07, ...etc...)
IV	Cable type and length (for products with integrated cable)	
	L••	: Standard flexible cord (PVC insulation), lateral output (•• = one or two digits giving the cable length in meter)
	LA••	: Standard flexible cord (PVC insulation), axial output (•• = one or two digits giving the cable length in meter)
V	Additional digit for operating head position (for products with pre-assembled head)	
	Blank or 0	: Head in "zero" position (catalog position)
	A	: Head at 15°
	B	: Head at 30°
	C	: Head at 45°
	...	: (every 15°)
	W	: Head at 345°
VI	Additional digit for operating lever position (for products with pre-assembled head)	
	Blank or 0	: Lever in "zero" position (catalog position)
	A	: Lever at 15°
	B	: Lever at 30°
	C	: Lever at 45°
	...	: (every 15°)
	W	: Lever at 345°
VII	Additional digit for operating lever orientation (for products with pre-assembled head)	
	Blank	: Normal orientation (catalog position)
	SR	: Inverted lever
VIII	Additional suffix for specific packaging	
	Blank	: Normal packaging (unitary)
	TQ	: Bulk packaging (this suffix only appears on the bulk packaging label, it does not appear on the product)

Manufacturer :
TMSS France
Tour Egho – 2 avenue Gambetta
92400 Courbevoie – FRANCE

UK Representative :
Yageo TMSS UK Limited
2 North Park Road
Harrogate, HG1 5PA – UNITED KINGDOM

Technical Documentation authority :
TMSS France
Boulevard Salvador Allende – ZI n°3
16340 L'Isle d'Espagnac – FRANCE