

EU Declaration of Conformity

Nr : PKR3338100-02

Products identification :

Type of products : Limit switches

Trademark : **Telemecanique Sensors**

Models : **XCMH...**

(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following European Directive(s) :

Low Voltage Directive : **2014/35/EU**

EMC Directive : **2014/30/EU**

RoHS Directive : **2011/65/EU + 2015/863**

Product's conformity has been assessed by applying the following harmonized standard(s) :

EN 60947-5-1:2017 + AC:2020

EN IEC 63000:2018


When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.

Gregory POUX

Customer Satisfaction & Quality Director

Issued at : L'Isle d'Espagnac – FRANCE

Emission date : February 27th, 2024



Appendix

Nr : PKR3338100-02

List of product models covered by the present EU Declaration of Conformity

XCMH	21	15	L2	F	0	SR	TQ
I	II	III	IV	V	VI	VII	VIII

I	Body type	
	XCMH	: Optimum miniature plastic limit switch
II	Contact block type	
	21	: NO+NC snap action
	29	: NC+NC snap action
III	Operating head type	
	nn	: All existing ZCE heads (nn = 02 for ZCE02, nn = 07 for ZCE07, ...etc...)
IV	Cable type and length (for products with integrated cable)	
	L**	: Standard flexible cord (PVC insulation), lateral output (* = one or two digits giving the cable length in meter)
	LA**	: Standard flexible cord (PVC insulation), axial output (* = one or two digits giving the cable length in meter)
V	Additional digit for operating head position (for products with pre-assembled head)	
	Blank or 0	: Head in "zero" position (catalog position)
	A	: Head at 15°
	B	: Head at 30°
	C	: Head at 45°
	...	: (every 15°)
VI	Additional digit for operating lever position (for products with pre-assembled head)	
	Blank or 0	: Lever in "zero" position (catalog position)
	A	: Lever at 15°
	B	: Lever at 30°
	C	: Lever at 45°
	...	: (every 15°)
VII	Additional digit for operating lever orientation (for products with pre-assembled head)	
	Blank	: Normal orientation (catalog position)
	SR	: Inverted lever
VIII	Additional suffix for specific packaging	
	Blank	: Normal packaging (unitary)
	TQ	: Bulk packaging (this suffix only appears on the bulk packaging label, it does not appear on the product)