

EC/EU Declaration of Conformity

Nr : BQT8605700-00

Products identification :

Type of products : Emergency stop trip wire switches

Trademark : **Telemecanique Sensors**

Models : **XY2CE1..., XY2CE2..., XY2CE5..., XY2CE6..., XY2CED...**
(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following European Directive(s) :

Machinery Directive : **2006/42/EC**

Low Voltage Directive : **2014/35/EU**

EMC Directive : **2014/30/EU**

RoHS Directive : **2011/65/EU + 2015/863**

Product's conformity has been assessed by applying the following harmonized standard(s) :

EN ISO 13849-1:2015

EN ISO 13850:2015

EN 60204-1:2018

EN 60947-5-1:2017 + AC:2020

EN 60947-5-5:1997 + A1:2005 + A11:2013 + A2:2017

EN IEC 63000:2018

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.

Gregory POUX

Customer Satisfaction & Quality Director

Issued at : L'Isle d'Espagnac – FRANCE

Emission date : February 7th, 2024



TMSS France

Postal address :
Tour Eqho – 2 avenue Gambetta
92400 Courbevoie – FRANCE

Technical Documentation authority :

TMSS France
Boulevard Salvador Allende – ZI n° 3
16340 L'Isle d'Espagnac – FRANCE

Appendix

Nr : BQT8605700-00

List of product models covered by the present EC/EU Declaration of Conformity

XY2CE	1	C	2	5	0	H7	TK
I	II	III	IV	V	VI	VII	VIII

I	Product type	
	XY2CE	: Rope pull switch with single or double anchor point
II	Position of the anchor point(s) and tripping force	
	1	: 1 anchor point on right side, standard tripping force
	2	: 1 anchor point on left side, standard tripping force
	5	: 1 anchor point on right side, light tripping force
	6	: 1 anchor point on left side, light tripping force
D	: 2 anchor points on left and right sides, standard tripping force	
III	Cable tension indicator and type of protection bellow(s)	
	A	: Without cable tension indicator, Nitrile bellow(s)
	C	: Without cable tension indicator, Silicone bellow(s)
	D	: With cable tension indicator, Nitrile bellow(s)
E	: With cable tension indicator, Silicone bellow(s)	
IV	Type of reset	
	1	: Flush pushbutton
	2	: Booted pushbutton
	3	: Ø30 mushroom head pushbutton
	4	: Ø30 mushroom head pushbutton, operated by key n° 421
5	: Ø30 mushroom head pushbutton, operated by key n° 455	
V	Contacts type for stop function	
	5	: 1 NC + 1 NO, slow break (break before make)
	7	: 2 NC, slow break
9	: 2 NC + 2 NO, slow break (break before make)	
VI	Pilot light type and supply voltage	
	0	: Without pilot light
	6	: With 24 V to 130 V AC or DC pilot light
7	: With 230 / 240 V AC pilot light	
VII	Optional : Additional digit for cable entries type	
	Blank	: Smooth holes for PG 13,5 or ISO M20 x 1,5 cable gland
H7	: Threaded holes for 1/2" NPT cable gland	
VIII	Optional : Additional digit for protective treatment type	
	Blank	: Normal protection
TK	: Increased protection against corrosion	

NOTE : These references may be followed by 1 to 3 alphanumeric digits, to denote assembly, marking or packaging variations, without impact on products characteristics and/or compliance.