



EU Declaration of Conformity

Nr : BRU1280700-00

Products identification :

Type of products : Limit switches

Trademark : **Telemecanique Sensors**

Models : **XCKMR..., XCKVR...**

(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following European Directive(s) :

Low Voltage Directive : **2014/35/EU**

EMC Directive : **2014/30/EU**

RoHS Directive : **2011/65/EU + 2015/863**

Product's conformity has been assessed by applying the following harmonized standard(s) :

EN 60947-5-1:2017 + AC:2020

EN IEC 63000:2018

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.

Gregory POUX

Customer Satisfaction & Quality Director

Issued at : L'Isle d'Espagnac – FRANCE

Emission date : March 19th, 2024

Appendix

Nr : BRU1280700-00

List of product models covered by the present EU Declaration of Conformity

XCKMR	54	D	1	H29	L30
I	II	III	IV	V	VI

I	Product type	
	XCKMR	: Metal limit switch for hoisting and material handling applications
	XCKVR	: Plastic limit switch for hoisting and material handling applications
II	Contact block type	
	24	: 2 x NO+NC, slow break (break before make), "By-pass" operating mode
	44	: 2 x NO+NC, slow break (break before make), "Single speed" operating mode
	54	: 2 x NC+NC, slow break (staggered), "Double speed" operating mode
III	Operating mode	
	D	: "Single speed" or "Double speed"
	SR	: "By-pass"
IV	Head orientation	
	1	: Normal head orientation (cruciform rods facing front side of the product)
	2	: Reversed head orientation (cruciform rods facing back side of the product)
V	Cable entry type	
	Blank	: Threaded holes for PG 13,5 cable gland
	H29	: Threaded holes for ISO M20 x 1,5 cable gland
VI	Additional suffix for specific features	
	Blank	: Basic version (catalog version)
	L30	: Specific version with 300 mm length rods

NOTE : These references may be followed by 1 to 3 alphanumeric digits, to denote assembly, marking or packaging variations, without impact on products characteristics and/or compliance.