

EU Declaration of Conformity

Nr : DN0000163-00

Products identification :

Type of products : Photoelectric proximity switches

Trademark : **Telemecanique Sensors**Models : **XUB...A... , XUB...B... , XUB...S...**

(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following European Directive(s) :

EMC Directive : **2014/30/EU**RoHS Directive : **2011/65/EU + 2015/863**

Product's conformity has been assessed by applying the following harmonized standard(s) :

EN IEC 60947-5-2:2020**EN IEC 63000:2018**

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.

Gregory POUX

Customer Satisfaction & Quality Director

Issued at : L'Isle d'Espagnac – FRANCE

Emission date : March 18th, 2025**TMSS France**

Postal address :

Tour Eqho – 2 avenue Gambetta
92400 Courbevoie – FRANCE<https://tesensors.com/global/en/support/technical-support>**Technical Documentation authority :****TMSS France**Boulevard Salvador Allende – ZI n° 3
16340 L'Isle d'Espagnac – FRANCE

Page : 1/2

Appendix

Nr : DN0000163-00

List of product models covered by the present EU Declaration of Conformity

XUB	2	A	P	A	N	L2	T
I	II	III	IV	V	VI	VII	VIII

I	Product type	
	XUB	: Photoelectric proximity switch, cylindrical shape, 18 mm diameter
II	Detection mode	
	0	: Multi-mode
	1	: Reflex
	2	: Thru-beam
	4	: Diffuse
	5	: Diffuse with adjustable sensitivity
III	Enclosure material	
	A	: Plastic
	B	: Nickel plated brass
	S	: Stainless steel
IV	Wiring scheme and output type	
	K	: DC 3 wires, without output (thru-beam transmitter), or programmable output (emitter/receiver)
	N	: DC 3 wires, with NPN output (only for receiver or emitter/receiver)
V	Output function	
	A	: NO
	B	: NC
	S	: NO or NC, programmable by "Teach" push-button (emitter/receiver only)
VI	Detection direction	
	N	: Axial detection
	W	: Lateral detection
VII	Type of connection	
	L••	: Standard flexible cord with PVC insulation (•• = one or two digits giving the cable length in meter)
	L08M12	: "Pigtail" (PVC insulation) 0,8 m length with M12 / 4 pins connector
	M12	: Connection by M12 / 4 pins connector
VIII	Additional suffix for particular function	
	Blank	: Emitter/receiver
	R	: Thru-beam receiver
	T	: Thru-beam transmitter

NOTE : These references may be followed by 1 to 3 alphanumeric digits, to denote assembly, marking or packaging variations, without impact on products characteristics and/or compliance.