

EU Declaration of Conformity

Nr : DN0000469-00

Products identification :

Type of products : Photoelectric proximity switches

Trademark : **Telemecanique Sensors**Models : **XUK•A••A...**, **XUK•A••N...**, **XUK•A••T...**
(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following European Directive(s) :

Low Voltage Directive : **2014/35/EU**EMC Directive : **2014/30/EU**RoHS Directive : **2011/65/EU + 2015/863**

Product's conformity has been assessed by applying the following harmonized standard(s) :

EN IEC 60947-5-2:2020**EN IEC 63000:2018**

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.

Didier BARON

President of Telemecanique Sensors PBU

Issued at : L'Isle d'Espagnac – FRANCE

Emission date : May 15th, 2025**TMSS France**Postal address :
Tour Eqho – 2 avenue Gambetta
92400 Courbevoie – FRANCE<https://tesensors.com/global/en/support/technical-support>**Technical Documentation authority :****TMSS France**
Boulevard Salvador Allende – ZI n° 3
16340 L'Isle d'Espagnac – FRANCE

Page : 1/2

Appendix

Nr : DN0000469-00

List of product models covered by the present EU Declaration of Conformity

XUK	2	A	P	A	N	L2	R
I	II	III	IV	V	VI	VII	VIII

I	Product type	
	XUK	: Compact photoelectric proximity switch
II	Detection mode	
	0	: Multi-mode
	1	: Reflex
	2	: Through-beam
	5	: Diffuse
	8	: Diffuse with background suppression
III	Enclosure material	
	A	: Plastic
IV	Wiring scheme and output type	
	K	: DC 3 wires, without output (through-beam transmitter), or programmable output (emitter/receiver)
	N	: DC 3 wires, with NPN output (only for receiver or emitter/receiver)
	P	: DC 3 wires, with PNP output (only for receiver or emitter/receiver)
	R	: AC/DC 5 wires, with C/O relay output (only for receiver or emitter/receiver)
V	Output function	
	A	: NO
	B	: NC
	C	: NO and NC (C/O relay output)
VI	Additional function	
	A	: With beam interruption input (through-beam transmitter), or alarm output (receiver or emitter/receiver)
	N	: No additional function
	T	: With time-delay output (only for receiver or emitter/receiver)
VII	Type of connection	
	L••	: Standard flexible cord (PVC insulation) (•• = one or two digits giving the cable length in meter)
	M12	: Connection by M12 / 4 pins connector
VIII	Additional suffix for particular function	
	Blank	: Emitter/receiver
	R	: Through-beam receiver
	T	: Through-beam transmitter

NOTE : These references may be followed by 1 to 3 alphanumeric digits, to denote assembly, marking or packaging variations, without impact on products characteristics and/or compliance.