

## EU Declaration of Conformity

Nr : DN0000644-00

**Products identification :**

Type of products : Severe duty limit switches for mill and foundry applications

Trademark : **Telemecanique Sensors**Models : **9007T..., 9007FT...**  
(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following European Directive(s) :

Low Voltage Directive : **2014/35/EU**EMC Directive : **2014/30/EU**

Product's conformity has been assessed by applying the following harmonized standard(s) :

**EN 60947-5-1:2017 + AC:2020**

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.

**Didier BARON**

President of Telemecanique Sensors PBU

Issued at : L'Isle d'Espagnac – FRANCE

Emission date : June 13<sup>th</sup>, 2025**TMSS France**Postal address :  
Tour Egho – 2 avenue Gambetta  
92400 Courbevoie – FRANCE**Technical Documentation authority :****TMSS France**  
Boulevard Salvador Allende – ZI n° 3  
16340 L'Isle d'Espagnac – FRANCE

## Appendix

Nr : DN0000644-00

List of product models covered by the present EU Declaration of Conformity

<b>9007FT</b>	<b>U</b>	<b>B</b>	<b>12</b>	<b>M11</b>
<b>I</b>	<b>II</b>	<b>III</b>	<b>IV</b>	<b>V</b>

<b>I</b>	<b>Product model</b>	
	<b>9007FT</b>	: Severe duty limit switch for foundry applications, metallic enclosure
	<b>9007T</b>	: Severe duty limit switch for mill applications, metallic enclosure
<b>II</b>	<b>Product and contact block type</b>	
	<b>S</b>	: Universal type, 1 pole, NO+NC, snap action
	<b>U</b>	: Standard type, 1 pole, NO+NC, snap action
	<b>Y</b>	: Universal type, 1 pole, NO+NC (three points contact), snap action
<b>III</b>	<b>Base fixing mode</b>	
	<b>A</b>	: No mounting holes in baseplate, two tapped holes on each side of switch allows side mounting
	<b>B</b>	: Four mounting holes in baseplate, holes pitch 4.22 in. x 1.81 in. (107,12 mm x 45,97 mm)
	<b>C</b>	: Four mounting holes in baseplate, holes pitch 2.44 in. x 2.81 in. (61,98 mm x 71,37 mm)
	<b>D</b>	: Four mounting holes in baseplate, holes pitch 4.31 in. x 1.75 in. (109,47 mm x 44,45 mm)
<b>IV</b>	<b>Operating sequence</b>	
	<b>nn</b>	: 1 or 2 numeric digits defining the product's operating sequence (15 available)
<b>V</b>	<b>Cable entry type</b>	
	<b>Blank</b>	: Threaded hole for 1/2" NPT cable gland
	<b>M11</b>	: Threaded hole for ISO M20x1,5 cable gland
	<b>M12</b>	: Threaded hole for ISO PG13,5 cable gland